FLEXIBLE RACK

Aluminium

This rack offers optimal flexibility.

Equipped with adjustable shelves and by sliding one or more shelves to the bottom, the headroom between the remaining shelves increases and consequently allows the use of larger cages.





FLEXIBLE RACK Aluminium

PRODUCT CODE

07-FLEX-ST-JUST-7 (a total of 7 shelves, 6 shelves are adjustable; the bottom shelf is fixed)

MATERIALS

The rack is made in anodised aluminium tubes (25 x 25 mm).

The plastic grid shelves are made in reinforced Polypropylene plastic.

Grid spacing of 66 x 40 mm.

4 not-autoclavable wheels (125 mm Ø), 2 with brake.

SPECIFICATIONS

Shelf distance: 230 mm.

The plastic grid shelves are mounted in the rack with specially designed rubber suspension fittings, which absorb expansion during autoclaving, plus they reduce noise and vibration.

Sloping roof.

CAPACITY (EXAMPLES)

15 European standard cages type 1354G (IV) (if 5 shelves are in use)
24 European standard cages type 1290D (III) (if 6 shelves are in use)
35 European standard cages type 1284L (II-L)
70 European standard cages type 1264C (II) (if placed in double row)

DIMENSIONS

W 1342 x D 580 x H 1950 mm.

OPTIONS

The rack is also available with 5, 6 or 8 shelves:

- 07-FLEX-ST-JUST-5
 (a total of 5 shelves, 4 shelves are adjustable; the bottom shelf is fixed)
- 07-FLEX-ST-JUST-6
 (a total of 6 shelves, 5 shelves are adjustable;
 the bottom shelf is fixed)
- 07-FLEX-ST-JUST-8

 (a total of 8 shelves, 7 shelves are adjustable;
 the bottom shelf is fixed)

WASHING/CLEANING

The rack is washable at up to 75°C.

As frequent washing of aluminium racks with alkaline cleaning products may cause changes in the surface, we recommend that you to use a neutral or acidic detergent with a pH value of 7 or lower.

The plastic grid shelves are autoclavable at 121°C.

The sloping roof drains water off.

